



常用规格技术数 General Electrical data

Part Number	Cap (μF)	L (mm)	T (mm)	H (mm)	P (mm)	P1 (mm)	du/dt (v/μs)	I _{rms} @45°C @10kHz	Output insert
Un 2000v.dc Us 750v.ac									
CTR3000J2×0.4-#	2×0.4	155	76	44	28	40	1500	2×45	3×M6
CTR3000J2×0.6-#	2×0.6	155	76	44	28	40	1500	2×50	3×M6
CTR3000J2×0.65-#	2×0.65	155	76	44	28	40	1500	2×50	3×M6
CTR3000J2×0.7-#	2×0.7	155	76	44	28	40	1500	2×60	3×M6
CTR3000J2×0.75-#	2×0.75	155	76	44	28	40	1500	2×65	3×M6
CTR3000J2×0.8-#	2×0.8	155	76	44	28	40	1500	2×68	3×M6
CTR3000J2×0.9-#	2×0.9	155	76	44	28	40	1500	2×70	3×M6
CTR3000J2×0.96-#	2×0.96	155	76	44	28	40	1500	2×72	3×M6
CTR3000J2×1.0-#	2×1.0	155	76	44	28	40	1500	2×75	3×M6
CTR3000J2×1.15-#	2×1.15	155	76	44	28	40	1500	2×80	3×M6
CTR3000J2×1.2-#	2×1.2	155	76	44	28	40	1500	2×80	3×M6
CTR3000J2×1.35-#	2×1.35	155	76	44	28	40	1500	2×85	3×M6

产品编码说明:

CTR3000J2×1.0-M6-155 “M6”=output “155”=Length